



1120 - Wireless Force Accelerometer

Version: 1.0 | DS166

Table of contents

Introduction	3
Pack Contents	5
Operational Overview	6
Connectivity	8
Charging the Sensor	9
Firmware Updates	10
Usage Information	11
Practical Investigations	12
Sensor Specifications	14
Limited Warranty	15
Compliance	16
Troubleshooting	17
Notices	18
Contact Information	19
PDF Translations	20

Introduction

Thank you for purchasing the Smart Wireless Force Accelerometer. We pride ourselves on producing high quality products that meet with the demands of the busy classroom environment. If you have any problems using this sensor, please read this documentation in full before contacting the Data Harvest support team.



Overview

The Wireless Force sensor has a:

- Force sensor that can measure forces in the range -100 to + 100 N
- An acceleration sensor that can measure accelerations in the range 0 to 150m/s² along three axis (at one time)
- A Gyroscope sensor that can measure rotation about three axis (one at a time) in the range 0 to 8m/s

The force sensor is an aluminium load cell with a 3mm threaded connection point. The gyro and acceleration are silicon mems sensors mounted on the circuit board.

A pair of holes at the top of the sensor allows the user to hold the sensor using their fingers, between the finger holes is a smaller ovoid hole with a screw to fix the sensor firmly to a metal rod, the ovoid shape of the hole ensures the connecting rod is centralised with respect to the hole.

The sensor is a versatile piece of apparatus that will allow an investigator, for example, to study force changes in a pendulum swing. Force – extension for Hooke's law, impulse, and static and kinetic friction. The accelerometer can be used to show g, free fall and $F=ma$.

The sensors can record at high speed (50 us between samples) if it is the only sensor connected. Number of ranges in use from the same sensor will not affect this. However, if you connect additional sensors the intersample time will increase

Pack Contents

This product is supplied with the following items:

- 1 x Smart Wireless Force Accelerometer
- 1 x USB Connecting Lead
- 1 x Hook
- 1 x Rubber Buffer
- 1 x Plastic Hard Buffer


Additional Accessories

To get the most from your Smart Force Accelerometer, the following items should be considered:

- [Wireless Motion Sensor](#)
 - [Wireless Dynamics System](#)
-

Operational Overview

The diagram below shows the specific parts of the sensor. Read further to explore the functionality of each part of the sensor.



- 1. Load connection point
- 2. Finger grips
- 3. Mounting point
- 4. Status Indicator
- 5. On/Off Switch
- 6. USB Port
- 7. Unique ID Number

Load connection point (1)

This is a threaded hole into the aluminium load cell. It has a thread size of 3mm. Care needs to be taken when screwing rings, hooks, buffers into the load cell so that the thread does not go through the cell and connect to the far side of the cell, locking it in position. Only screw any attachment in for a distance that gives the attachment a good grip into the cell. Typically, this would be no more than 5mm. When you use the supplied hook / ring a white threaded lock washer is supplied to prevent over insertion.

Finger grips (2)




For use if holding loads from your hands or pulling and pushing the sensor against objects.






Mounting point (3)

Typically this would be used to hold the force sensor onto a rod (for example a rod connected to a mounting boss on a ring stand)

The Status Indicators (4)

The sensor features a single status indicator that changes colour and flashes. See the table below for further information.

Status Light		Indicates
No light		Sensor is Off. Short press the On/Off switch
Blue flashing		Sensor is On and Bluetooth advertising
White flashing		Charging via USB mains charger or USB port, Sensor is On and Bluetooth advertising

Red, Green, Blue Flashing		Charging via USB mains charger or USB port, Sensor is Off
Green flashing		Communication with the EasySense2 app (via USB or Bluetooth) has been established
Solid Green		Fully charged
Orange flashing		Recording data
Red flashing		Battery is low

On/Off Switch (5)

The sensor's on/off switch allows you to turn the sensor on, off or perform a hard reset.

To switch the sensor off

- Press and hold down the On/Off switch until the white light shows, then release.
- If not communicating with the EasySense2 app, the sensor will turn off after a period of one hour of inactivity.

Hard resetting the sensor

- If necessary, attach the sensor to power.
- Press and hold down the On/Off button for at least 8 seconds until the status LED gives a flash of blue light, then release.
- If the sensor fails to respond, contact Product Support at Data Harvest. Please provide details of:
 - The computer platform it is being used with and the EasySense2 app's version number.
 - A description of the problem being encountered.

USB Port (6)

Use to connect to a computer or a charging unit.

For specific USB or Bluetooth connectivity instructions, please see the 'Connectivity' section of this documentation.

For instructions on charging your device, see the section on 'Charging the Sensor'.

Unique ID Number (7)

All Smart Wireless Sensors are labelled with a unique ID number. This number is used in the EasySense2 app, so that you can identify each sensor when making a connection wirelessly.

Connectivity

The sensor is both USB and Bluetooth compatible. Install the EasySense2 app, if it is not already on your device. For details of how to operate the EasySense2 app, please refer to the EasySense2 documentation.

USB Connectivity

Quick Steps

1. Connect the sensor to the computer's USB port using the USB cable supplied.
2. The computer will automatically detect a new device and depending on your operating system, will install any applicable device drivers.
3. Start EasySense 2 app.
4. Within the EasySense2 app, the Devices icon will change to green to show that the sensor is connected, and the status light on the sensor will also turn green.
5. Begin your practical investigations.

Bluetooth Connectivity

Using Bluetooth, the sensor can wirelessly connect to mobile devices such tablets and mobile phones, as well as desktop or laptop computers, giving students the ability to run experiments independently without being tethered to a device.

See the EasySense2 app user manual system requirements for further details.

Quick Notes on Bluetooth Connectivity

Only use with the EasySense2 app, you do not need to pair the device. If paired, the sensor will not be available to the EasySense2 app.

Computers or devices will need to support Bluetooth Low Energy (BLE). For further information refer to the instructions provided for the EasySense2 app.

Quick Steps

1. Short press the on/off switch to turn the sensor on, blue LED will flash.
 2. Open the EasySense2 app.
 3. Select the Devices icon.
 4. Select your sensor from the list of available sensors to connect to the device. Your sensor is identified by its unique ID in the list.
 5. Click on connect at the side of your sensor in the list.
 6. The Devices icon will change to green and the status light on the sensor will flash green to indicate a connection has been established.
 7. Begin your practical investigations.
-

Charging the Sensor

The Smart Wireless sensors are fitted with a rechargeable lithium-ion battery and can be charged via the USB port. Use the supplied USB lead to connect the sensor either directly to a USB port on your computer, a powered USB hub or a USB mains charger that outputs 5 V at 500 mA or more.

A full charge can take up to 4 hours.

Additional Information

Whenever the sensor is connected to the USB port on the computer or to a USB mains charger (output 5 V at 500 mA or more), it will automatically recharge the battery (LED status flashing white).

When connected to a computer, the computer should be turned on and not in sleep or standby mode, as the battery may drain instead of charge.

The sensor will stay awake for 5 minutes when Bluetooth advertising (LED status flashing blue).

Lithium-ion batteries are 'memory-free' and prefer a partial rather than a full discharge. Constant partial discharges with frequent recharges will not cause any harm. Frequent full discharges should be avoided whenever possible. Ideally the sensor should be stored at about 40% or more charge.

The speed at which a lithium-ion battery will age is governed by both its storage temperature (preferably less than 40 C) and state-of-charge.

Firmware Updates

Occasionally Data Harvest may release updated firmware which will contain improvements or new features.

Updates will take place when you connect your sensor to the EasySense2 app. You will be given the option to decline an update.

Updates can be performed over USB or Bluetooth and will typically take less than one minute. Updating firmware over USB will be quicker than Bluetooth.

Do not disconnect the sensor, or power off during the update.

If you have a wireless connection to the EasySense2 app, the sensor will have to be reconnected after performing the update.

Usage Information

Care must be taken to not overload the load cell. Its range is ± 100 N (10 kg). This is for loading and unloading the cell for a practical such as Hook's law.

For changes in force with time impulse you will need to carefully test the limits. For example, a drop onto the hard buffer from 10cm will give a maximum force of 10 N using the mass of the sensor package only.

Collisions can generate peak loads much higher, a cart colliding with the sensor can easily reach 95 N.

When using attachments to the load cell, make sure the thread of the attachment does not go through the cell and lock the cell or restrict its movement. A thread insertion of 5mm will be sufficient in most cases.

A flat headed attachment will be used to push the sensor against an object or provide a buffer for impulse and collision work.

Make sure the attachment sits proud of the case to allow contact with the practical.

For collisions, use the shortest intersample time available; for SHM and suspended masses, use 10ms. Exactly which data collection speed will give the best recording depends upon the stiffness of the spring used and the mass suspended.

The software contains a Tare function to let you set the Zero point.

The user set up for the data collection lets you set triggers and recording durations to co-ordinate start and end points.

Practical Investigations

The Smart Wireless Force Accelerometer can be used to investigate a number of scientific experiments such as:

- Hooke's law
- Forces in a suspended mass spring system
- Bungee jump
- Period of oscillation of suspended mass on a spring
- Friction studies
- Forces and interactions
- Collisions and impulse
- Showing g and free fall

Online Videos

Learn how to use data logging in the classroom with our Secondary Science Academy demonstration videos, which will walk you through using the new EasySense2 app and show you how to get hands-on with the latest Bluetooth wireless sensors. The video experiments will show you how to get the best out of your science lessons.

New online content is being continuously uploaded onto our YouTube channel, including practical worksheets as well as videos.


See our website for further information and links.



Explore Bluetooth Sensors

Are you looking to make the jump to our smart wireless sensors? Or have you recently purchased them and want to know more about how they work?

[View video playlist](#)



Explore EasySense2

The core of our science platform is our EasySense2 software. In these videos you will learn everything from the basics of our software to the most in-depth features.

[View video playlist](#)



Explore Science Practicals

See our Smart Wireless Sensors in action with a range of practical experiments. This is the best way to get started with the new Bluetooth sensors!

[View video playlist](#)

Sensor Specifications

Please read the following table for sensor specifications.

Feature	Detail
Measurement Ranges	Force: $\pm 100\text{N}$ Acceleration XYZ and Resultant: $\pm 40\text{m/s}^2$, $\pm 150\text{m/s}^2$ ($\pm 4\text{g}$, $\pm 16\text{g}$) Gyroscope XYZ: $\pm 8\text{rad/s}$ ($\pm 500\text{dps}$)
Resolution	0.01N
Maximum Load	$\pm 120\text{N}$
Fastest logging speed	Force: $500\mu\text{s}$ (2000Hz) Acceleration: 1ms (1000Hz) Gyroscope: 1ms (1000Hz)
Connectivity	Wired via USB Wireless via Bluetooth
Bluetooth Specifications	Bluetooth 4.2 low energy radio, single mode compliant Transmit (TX) power: 0 dBm Receiver (RX) sensitivity: - 90 dBm Usable transmission range: up to 10 m in open air Frequency Range: 2.402 to 2.480 GHz operation
Internal Battery	Rechargeable internal lithium-ion 3.7 V Power specification: 5 V at 500 mA
Storage/Operating Temperature	0 - 40 C
Humidity	0 to 95% RH (non-condensing)
Physical Specifications	Weight: approx. 125 g External dimensions: approx. height 27 mm x width 71 mm x length 112 mm

Limited Warranty

For information about the terms of the product warranty, see the Data Harvest website at: <https://data-harvest.co.uk/warranty>

Product Repairs

When returning goods to Data Harvest, please download and complete the repair return [form](#) to ensure you have sent us all the information we require, and send it to us alongside the item to be repaired. The second page of this form includes a return address label.

If you have purchased a Data Harvest manufactured product via a different company, please also supply proof of purchase.

Postage Charges

- In the event of a fault developing, the product must be returned in suitable packaging to Data Harvest for repair or replacement at no expense to the user other than postal charges.
- There will be no postal charge for the return of repaired goods to any mainland UK address (for other areas, additional shipping charges may apply).

Out of Warranty Repairs

Please visit <https://data-harvest.co.uk/repairs> for the most up to date charges for out of warranty repairs.

Warranty on Repaired Items

Once an item has been serviced and repaired, the product will have 1 year warranty against further failure of the component repaired.

International Returns

Please contact the authorised Data Harvest representative in your country for assistance in returning equipment for repair.

Compliance

This product complies to the following standards

Waste Electrical and Electronic Equipment Legislation

Data Harvest Group Ltd is fully compliant with WEEE legislation and is pleased to provide a disposal service for any of our products when their life expires. Simply return them to us clearly identified as 'life expired' and we will dispose of them for you.

FCC Details


This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

CE

This product conforms to the CE specification. It has been assessed and deemed to meet EU safety, health and environmental protection requirements as required for products manufactured anywhere in the world that are then marketed within the EU.

UKCA

This product conforms to the UKCA specifications.



Troubleshooting

If you experience any problems with your product, please try the following troubleshooting tips before contacting the Data Harvest support team.

Feature	Detail
Loss of Bluetooth Connectivity	<p>If the sensor loses Bluetooth connection and will not reconnect try:</p> <p>Closing and reopening the EasySense 2 app.</p> <p>Switching the sensor Off and then On again.</p> <p>If you are using a Bluetooth Smart USB Adaptor on your computer, unplug the adaptor, plug back in again and try to reconnect.</p> <p>Hard reset the sensor and then try to reconnect.</p>

Notices

CONTENT REQUIRED

Please read the following notices with regards to using your sensor

1. The sensor is much smarter than traditional Bluetooth sensors and you are not required to pair the device. If paired, the sensor will not be available to the EasySense 2 app.
 2. When the sensor is connected to a computer, the computer should be turned on and not in sleep or standby mode or the battery may drain instead of charge.
 3. Data Harvest products are designed for educational use and are not intended for use in industrial, medical or commercial applications.
 4. The sensor is not waterproof.
 5. Plastic parts may fade or discolour over time if exposed to UV light. This is normal and will not affect the operation of the sensor.
-

Contact Information

To contact Data Harvest directly, please use any of the following channels

Traditional Communications

Data Harvest Group Ltd.
1 Eden Court, Eden Way,
Leighton Buzzard,
Bedfordshire,
LU7 4FY
United Kingdom

Tel: +44 (0) 1525 373666

Fax: +44 (0) 1525 851638

Sales email: sales@data-harvest.co.uk

Support email: support@data-harvest.co.uk

Online Communications

We have active social media support channels using the following platforms

- [Facebook](#)
- [Twitter](#)
- [YouTube](#)

Office Opening Hours

Monday to Thursday - 08:30 to 16:45

Friday - 08:30 to 13:30

Saturday & Sunday & UK Bank Holidays - Closed

PDF Translations

The PDF formatted download of this manual is by default provided in the English (United Kingdom) language. If an alternative translation is available, it will be listed here.

We have for your convenience included a webpage translation feature to the online documentation which will allow you to translate and print individual pages of this documentation.
